

IN THE U.S. PATENT AND TRADEMARK OFFICE  
Patent Application Transmittal Letter

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 CFR 1.53(b) is a(n): ☒ Utility ☐ Design

☒ original patent application,  
☐ continuation-in-part application

INVENTOR(S): Terry A. Smith et al

TITLE: System For Printing A Document With Recurring Images

Enclosed are:

- ☒ The Declaration and Power of Attorney. ☒ signed ☐ unsigned or partially signed  
☒ 10 sheets of drawings (one set) ☐ Associate Power of Attorney  
☒ Form PTO-1449 ☐ Information Disclosure Statement and Form PTO-1449  
☐ Priority document(s) ☐ (Other) (fee \$ )

CLAIMS AS FILED BY OTHER THAN A SMALL ENTITY				
(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) TOTALS
TOTAL CLAIMS	20 — 20	0	X \$18	\$ 0
INDEPENDENT CLAIMS	3 — 3	0	X \$78	\$ 0
ANY MULTIPLE DEPENDENT CLAIMS	0		\$260	\$ 0
BASIC FEE: Design \$310.00 ); Utility \$690.00 )				\$ 690
TOTAL FILING FEE				\$ 690
OTHER FEES				\$
TOTAL CHARGES TO DEPOSIT ACCOUNT				\$ 690

Charge \$ 690 to Deposit Account 08-2025. At any time during the pendency of this application, please charge any fees required or credit any over payment to Deposit Account 08-2025 pursuant to 37 CFR 1.25. Additionally please charge any fees to Deposit Account 08-2025 under 37 CFR 1.16, 1.17, 1.19, 1.20 and 1.21. A duplicate copy of this sheet is enclosed.

"Express Mail" label no. EH862490632US

Date of Deposit July 21, 2000

I hereby certify that this is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231.

By Terri Walker

Typed Name: Terri Walker

Respectfully submitted,

Terry A. Smith et al

By

Matthew L. Wade

Attorney/Agent for Applicant(s)  
Reg. No. 42,206

Date: July 21, 2000

Telephone No.: (208) 396-5263

"Express Mail" mailing label number EH862490632US

Date of Deposit July 21, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" services under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner for Patents, Washington, D.C. 20231.

Typed Name of Person Mailing Paper or Fee: Terri walker

Signature: *Terri Walker*

**PATENT APPLICATION  
DOCKET NO. 10991929-1**

**SYSTEM FOR PRINTING A DOCUMENT WITH RECURRING IMAGES**

**INVENTORS:**

Terry A. Smith  
John F. Mauzey

# SYSTEM FOR PRINTING A DOCUMENT WITH RECURRING IMAGES

## CROSS REFERENCE TO RELATED APPLICATIONS

This application includes subject matter related to the co-pending application entitled "SYSTEM FOR PRINTING A DOCUMENT INCLUDING A FIXED FORM" having attorney docket number 10005207-1. That application is  
5 incorporated herein by reference, assigned to the same assignee as this application, and filed on even data herewith.

## BACKGROUND OF THE INVENTION

A typical printing system includes a personal computer and a printer. The computer is connected to the printer by a communication link, such  
10 as a network. The computer is used to generate a document and to then send the document to the printer for printing. The document is sent in the form of page description language (PDL) commands. These commands describe the document. The printer receives these commands and responds by printing the document. "PCL" and "POSTSCRIPT" are each examples of a PDL. PCL is a  
15 trademark of the Hewlett-Packard Corporation. POSTSCRIPT is a trademark of Adobe systems incorporated.

Documents often include an image that occurs more than once in a document. For ease of discussion, such an image is referred to herein as a "form". An example of a form may be a company letterhead or a company logo  
20 that occurs on each page in a document. An "instance" of the form refers to a particular one of the recurring images.

Current versions of POSTSCRIPT and PCL provide language specific constructs that allow a named sequence of PDL commands to represent a form. For ease of discussion, it will be understood that the phrase "named  
25 sequence" as used herein refers to a set of PDL commands that describe a form.

In general, the use of a named sequence can eliminate the need for a computer to repeatedly send the same set of commands to print each instance of a form in a document. As a result, the use of a named sequence can reduce

the amount of data that need be transmitted to a printer in order to print a document.

PCL version 6.0, for example, allows for a named sequence to be defined using the "Macro" commands. A Macro is a group of PCL commands that is given a name in the form of an identification number. Once stored in the printer memory, a macro can be executed repeatedly by additional command that calls the Identification number of the macro. Versions of the POSTSCRIPT language include similar capability.

The amount of time it takes to print a document is a significant factor in that printer's success in the marketplace. Thus, there is a strong interest in developing techniques to improve the printing speed of a printer. For purposes of this document, the phrase "printing speed" refers to the amount of time it takes for a printer to print a particular document. This time is measured from when the print job is first received by the printer until when the document is completely printed.

Accordingly, techniques that can improve the storage efficiency and speed at which a printer can process and print a named sequence are needed as this can increase the overall printing speed of a document.

#### SUMMARY OF THE INVENTION

Briefly and in general terms, a printer according to an embodiment of the invention includes an input/output (I/O) port, a control unit and a print engine. The I/O port is capable of receiving PDL commands describing a document. These commands may include a named sequence describing a form and an indicator. The indicator may indicate that permission is granted to print each instance of the form from the same video data. Alternatively, the indicator may indicate that each instance of the form is to be printed from new video data or that the form is a fixed form or that the form represents a background image. The control unit operates to process the named sequence based upon the information provided by the indicator.

The present invention may also be implemented as a method of processing and printing a named sequence of PDL commands that describe a

form. The method preferably includes receiving the named sequence and an associated parameter and responding to the parameter being set to a first value by converting the named sequence into video data and then using the video data to print each instance of the form. The method may also include the step  
5 of responding to the parameter being set to a second value by generating new video data to print each instance of the form. The named sequence and the parameter can be received from a source externally connected to the printer, such as a personal computer.

The present invention may also be implemented as a computer. A  
10 computer according to an embodiment of the invention includes a processor, a memory and an I/O port. The memory includes an application and a print driver. The application and the print driver are executed by the processor and enable the computer to generate a plurality of PDL commands that describe a  
15 form and at least one command indicating permission is granted to convert the named sequence once into video data and to then print each instance of the form from the video data. These PDL commands are transmitted over the I/O port to a printer for printing.

Other aspects and advantages of the present invention of the  
20 present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the invention.

#### DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a printing system incorporating an  
25 embodiment of the invention;

FIG. 2 illustrates a document that includes a background image and a foreground image;

FIG. 3 is a high level schematic of the computer and the printer shown in FIG. 1;

30 FIG. 4 is a flow chart illustrating the operation of the printer control unit upon receiving a set of PDL commands;

FIG. 5 is a flow chart illustrating the operation of the printer control unit according to the first algorithm;

FIG. 6 is a flow chart illustrating the operation of the printer control unit according to the second algorithm;

5           FIG. 7 is a flow diagram illustrating the operation of the printer control unit according to the third algorithm;

FIG. 8 illustrates a document that includes a form;

FIG. 9 illustrates a document that includes a "fixed form"; and

10           Fig. 10 illustrates yet another embodiment of the invention in the form of a program storage medium that includes a print job.

### DETAILED DESCRIPTION OF THE INVENTION

As shown in the drawings for purposes of illustration, the invention is embodied in a novel printing system that includes a computer and a printer. The computer is used to generate documents and to send the  
15   documents, in the form of PDL commands, to the printer for printing. Importantly, the computer is able to direct the printer to optimize the processing of a named sequence.

To introduce a first illustrative embodiment of the invention, FIG. 1 is a block diagram of a printing system 101. As shown, the printing system 101  
20   includes a computer 102 and a printer 104 connected via a communication link 106. The communication link 106 may represent any suitable means that allows the computer 102 to transmit PDL commands to the printer 104. Thus, the communication link 106 may represent a network (e.g., an intranet or the INTERNET) or a local port (e.g., a serial port or a parallel port).

25           It is important to note that the printing system 101 utilizes a page description language that, for ease of discussion, is referred to herein as the "system PDL". The system PDL may, for example, be an extended version of PCL or POSTSCRIPT. Importantly, the system PDL provides the utilities to:

- (a) represent a form by a named sequence of PDL commands; and
- 30       (b) define an "optimization parameter" to indicate certain information regarding the named sequence.

In the present embodiment, the optimization parameter has four predefined values. Table I lists the meaning of each of these four values for an associated named sequence.

Optimization Parameter value	Meaning for associated named sequence describing a form
Value #1	Each instance of the form is to be printed from new video data.
Value #2	Permission is granted to print each instance of the form from the same video data.
Value # 3	If new video data is generated to print each instance of the form, the new video data will, in each case, be identical (i.e., the form is a "fixed form").
Value #4	The named sequence represents a "background image".

TABLE 1

To illustrate the meaning of the phrase "background image", reference is briefly made to FIG. 2. FIG. 2 shows a two page document 202 that includes a background image. The background image is shown within box 204. The respective image on each page that overlaps the background image is referred to as herein as a "foreground image". The foreground image in page 1 of the document 202 is shown in box 206. The foreground image in page 2 is shown within box 208.

For purposes of the later discussion, video data that represents a background image is referred to herein as "background video data". Video data that represents a foreground image is referred to herein as "foreground video data".

FIG. 3 shows a high level schematic of the computer 102 and the printer 104. As shown in FIG. 3, the computer 102 includes a processor 308, a memory 310, an Input/output (I/O) port 312, and one or more user input devices 313. All these components are connected via a local bus 314. The I/O port 312 is used to couple the computer 102 to the communication link 106. The user

input device(s) 313 may include a standard keyboard and a pointer device. The processor 308 is used to execute programs stored in the memory 310. These programs include an application program (application) 312 and a print driver 314.

5           The printer 104 includes a control unit 350, a Random access memory (RAM) 356, an I/O port 352 and a laser print engine 358. All these components are connected via a local bus 360. As indicated, the RAM 356 includes a cache storage area 362 and a video buffer 364. Alternatively, or in addition, the printer 104 may include a local disk for use as a cache storage  
10   area.

          The control unit 350 operates under the direction of the firmware program 367 and provides both control and imaging facilities for the printer 104. As indicated, the control unit 350 includes a page description language interpreter module (PDLI) 368 and a raster image processor module (RIP) 370.  
15   Both of these modules may be implemented by firmware programs or hardware devices or by a combination of firmware and hardware devices.

          In general, a user of the computer 102 can provide input to the application 312 (via the user input devices 313) to generate a document. In response to further input from the user, the application 312 interacts with the  
20   print driver 314 to cause the print driver 314 to transmit the document, in the form of PDL commands, to the printer 104 for printing.

          Upon receiving the PDL commands over the I/O port 352, the control unit 350 responds by processing the commands to generate video data and to transmit the video data to the print engine 358. The print engine 358  
25   responds to the video data received from the video buffer 364 in a standard manner by generating printed output.

          As part of the processing operation performed by the control unit 350, the PDLI 368 is used to convert the PDL commands into display list data; the RIP 370 is used to convert the display list data into video data; the video  
30   buffer 364 is used to buffer the video data before being transmitted to the print engine 358. In addition, the control unit 350 manages the storage of the display list data and the video data in the RAM 356.



Fig. 4 illustrates the operation of the control unit 350 upon receiving a set of system PDL commands, from the computer 102, describing a document. The steps depicted in FIG. 4 are performed by the control unit 350 while operating under the direction of the firmware program 367. It is assumed that the set of commands include both a named sequence of commands  
5 describing a form. In addition, it is assumed that the set of commands further define an optimization parameter value for the named sequence.

Referring now to FIG. 4, the printer 104 begins receiving the PDL commands from the computer 102 over the I/O port 352 at step 402. The  
10 named sequence and the optimization parameter are received at step 404 and the rest of the PDL commands are received at step 406.

Importantly, the control unit 350 processes the named sequence based upon the value of the optimization parameter at step 408. The control unit 350 processes the rest of the PDL commands (received at step 402 and at  
15 step 406) at step 410. The control unit 350 transmits video data (via the video buffer 364) to the print engine 358 at step 412. The print engine 358 responds to the video data by printing the document.

Now let's consider in more detail the operation of the control unit 350 to process the named sequence at step 408.

If the optimization parameter is set to value #1 (indicating that each instance of the form is to be printed from new video data), the control unit  
20 350 operates to process the named sequence according to a first algorithm.

FIG. 5 is a flow diagram illustrating the operation of the control unit 350 to process the named sequence according to this first algorithm.

Referring now to FIG. 5, the control unit 350 begins processing the named sequence at step 502. The control unit 150 converts the named sequence into a display list (using the PDLI 368) and stores this data in the RAM 356 at step  
25 504.

Next, the control unit 350 flags the display list (generated at step  
30 504) as a candidate for caching (step 504). This indicates that this data will be accessed multiple time during the printing operation.

Next, the control unit 350 operates to print each instance of the form from the display list data (step 510). Thus, whenever video data is required to print an instance of the form, the display list data stored at step 504 is accessed from the RAM 356 and rendered by using the RIP 370. Importantly, this allows the RIP 370 to apply its optimization routines (e.g., halftoning), for enhancing print quality, each time the form is to be printed. Thus, as a result, each instance of the form is printed at an optimum print quality. It is noted for the later discussion, these routines may be dependant upon the spatial location of each instance of the form.

In the present embodiment, if the optimization parameter is set to value #2 or value #3, the control unit 350 operates to process the named sequence according to a second algorithm. As noted above, if the optimization parameter is set to value #2, this indicates that permission is granted to print each instance of the form from the same video data.

If the optimization parameter is set to value #3, this indicates that if new video data is generated to print each instance of the form, the new video data will, in each case, be identical. For purposes of this application a form that has this characteristic is referred to herein as a "fixed form".

FIG. 6 is a flow diagram illustrating the operation of the control unit 350 according to the second algorithm. Referring now to FIG. 6, the control unit 350 begins processing the named sequence at step 602. The control unit 350 converts the named sequence into a display list (using the PDLI 368) and stores this data in the RAM 356 at step 604.

Next, the control unit 350 analyzes the display list data to determine if the printing speed of the document would be increased if each instance of the form is printed from the same video data ( step 606). This is as opposed to the printing speed that can be obtained if the form were printed from display list data, thereby incurring the delay associated with rendering the display list data for each instance of the form.

If it is determined that printing speed is not increased if each instance of the form is printed from the same video data, then the control unit 350 essentially applies the first algorithm to process the named sequence

(decision step 607). Thus, the control unit 350 flags the display list data as a candidate for caching at step 608. Next, the control unit 350 operates to discard the named sequence at step 610 so as to release memory resources.

The control unit 350 then operates to print each instance of the form from the display list data (step 612). Thus, whenever video data is required to print an instance of the form, the display list data stored at step 604 is accessed from the RAM 356 and rendered by using the RIP 370. Importantly, this allows the RIP 370 to apply its optimization routines (e.g. halftoning routines) each time the form is to be printed. Thus, as a result, each instance of the form is printed at an optimum print quality.

If, however, it is determined that the printing speed is increased if each instance of the form is printed from the same video data, then the control unit 350 operates to convert the display list data into video data (using the RIP 370) and to then store this data in the RAM 356 (step 614). Next, the control unit 350 operates to discard the display list data and the named sequence so as to release memory resources (step 616). Next, the control unit 350 operates to use the video data stored at step 614 to print each instance of the form (step 618). Thus, as a result, each instance of the form is printed from the same video data. Importantly, the RIP 370 *is not able to apply* its optimization routines each time an instance of the form is to be printed. As a result, under some conditions, printing quality *may* be less than optimum. Document printing speed, however, is optimized.

It is noted that print quality is less than optimum only if the parameter value is set to value #2. If the parameter value is set to value #3, print quality remains at an optimum level. This is illustrated in the two examples described below.

If the optimization parameter is set to value #4, the control unit 350 operates to process the named sequence according to a third algorithm. As noted above, this indicates that the named sequence represents a background image.

FIG. 7 is a flow diagram illustrating the operation of the control unit 350 to process the named sequence according to the third algorithm.

Referring now to FIG. 7, the control unit 350 begins to process the named sequence at step 702. The control unit 350 operates to convert the named sequence into video data (by using the PDLI 368 and the RIP 370) and stores the video data into the RAM 356 at step 704. Next, the control unit 350 flags this video data as "background video data" at step 706. The control unit 350 then discards the named sequence received at step 702 and the display list generated at step 704 (step 707). This serves to release memory resources.

The control unit 350 then operates to print each page in the document that includes the background image by generating the foreground video for the page and then appropriately merging the background video data with the foreground video data (step 708). This is done so that the foreground image overlaps the background image. It is noted that one way this can be accomplished is by using the background video data to initialize the video buffer 364. The appropriate foreground video data is then written to video buffer 364 (thereby overwriting some or all of the background video data). Importantly, this is done so that the contents of the video buffer 364 represent the background image with the overlapping foreground image. The contents of the video buffer 364 are then transmitted to the print engine 358.

From the foregoing it will be appreciated that the printing system provided by the invention represents a significant advance in the art. The present invention provides a way for an application, executing in a computer, to control how a named sequence is processed by a printer. Moreover, the application can direct the printer to process a named sequence according to a printing algorithm that is most suitable for a given situation. For example, if the printing quality should be optimized over printing speed, the application can direct the printer to process the named sequence according to the first algorithm. If, however, printing speed is to be optimized over print quality, the application can direct the printer to process the named sequence according to the second printing algorithm.

To illustrate this and other advantages provided by this embodiment of the invention, consider the following examples.

### Example #1

Assume that the application 312 is used to generate a document 802 which is depicted in FIG. 8. As indicated, the document 802 includes a form which is labeled as "form A". Form A may represent any recurring image in the document such as a company logo. There are four instances of form A in the document 802: an instance 804, an instance 806, an instance 808 and an instance 810.

It is important to note that each instance of Form A is located spatially in a different location in the document 802. Thus, the following can be predicted:

(a) if a named sequence describing form A is processed by the control unit 350 according to the first algorithm, the print quality of form A is optimized. The printing speed of the document 802, however, may be less than optimum.

(b) if the same sequence describing form A is processed according to the second algorithm, the printing speed is optimized. The print quality, however, may be less than optimum.

Table 2 summarizes the comparative advantages and disadvantages of processing the named sequence describing form A under the first and the second printing algorithms.

	<b>First Printing Algorithm</b>	<b>Second Printing Algorithm</b>
Print Quality	Optimized	Less than optimum
Printing speed	less than optimum	Optimized

TABLE 2

Thus, it can be seen that if print quality is more important for a given situation or environment, the application 312 can be adapted to set the optimization parameter to "value #1". This directs the printer 104 to process the named sequence describing form A according to the first printing algorithm,

resulting in higher print quality. If, however, printing speed is considered more important, the application 312 can be adapted to set the optimization parameter to "value #2". This directs the printer 104 to process the named sequence according to the second algorithm. As a result, printing speed is optimized.

5                    In this manner the processing of the named sequence can be optimized for a given situation by setting the optimization parameter to the appropriate value.

#### Example #2

10                    In this example, assume that the application 312 is used to generate a document 902 which is depicted in FIG. 9. As indicated, the document 902 includes a form which is labeled as "form B". Form B may represent any recurring image in the document such as a company logo. There are two instances of form B in the document 902: an instance 904 and an instance 906.

15                    In this example, it is assumed that form B is a "fixed form". Thus, if a named sequence is converted to video data (first video data) to print the instance 904 and then converted again into video data (second video data) to print the instance 906, the first video data will be identical to the second video data.

20                    Table 3 summarizes the comparative advantages and disadvantages of processing the named sequence describing form B under the first and the second printing algorithm.

	<b>First Printing Algorithm</b>	<b>Second Printing Algorithm</b>
Print Quality	Optimized	Optimized
Printing speed	less than optimum	Optimized

25

TABLE 3

Thus, in this case it can be seen that there is no advantage in terms of print quality to process the form under the first printing algorithm as opposed to the second printing algorithm. As a result, in this example, the application 312 can be adapted to set the optimization parameter for the named sequence to "value #3". This results in the named sequence being processed according the second algorithm. As a result, printing speed is optimized.

The reader should note that the printer 104 in this embodiment applies the same printing algorithm to a named sequence if the optimization parameter is set to value #2 or value #3. In other embodiments, however, a printer incorporating the invention may respond differently to these two values.

For example, it may be desirable for certain types of printers to always preserve the print quality of a form. In such a case, the printer can be adapted to apply the first printing algorithm to process a named sequence if the associated optimization parameter is set to value #2. If the optimization parameter is set to value #3, the printer applies the second printing algorithm as no degradation in form print quality would be expected. Printing speed is, however, increased.

It is noted that in the embodiment just described, the functionality provided by both the application and the print driver may be provided by just the application alone. Thus, an application may be adapted to generate a named sequence of PDL commands and an associated optimization parameter without the use of a print driver.

It is also noted that the functionality provided by any one of the programs described above (e.g., the application 312, the print driver 314 and the control firmware 367) may alternatively be provided in whole or in part by hardware components. For example, one or more of the steps illustrated in FIGS. 3-7 could be performed by operation of an application specific integrated circuit having appropriate logic gates, a programmable gate array (s) (PGA) or a field programmable gate array (FPGA). It is also noted that in alternative embodiments of the present invention, the steps indicated in FIGS. 3-7 may occur out of the order indicated in these figures. For example, two steps shown in succession may be executed substantially concurrently or in reverse order.

In addition, a print job may include more than one named sequence. In such a case, each sequence may include an associated parameter and be processed according to one of the algorithms described above.

It is further noted that the present invention may also be embodied  
5 in the form of a program storage medium with computer readable program code embodied therein. The computer readable program may represent the application 312, the print driver 314, or the control firmware 367. In the context of this document, "program storage medium" can be any means that can contain, store, communicate, propagate, or transport the program for use  
10 by or in connection with an instruction execution system, apparatus or device. The program storage medium can be, for example (the following is a non-exhaustive list), a magnetic, optical, or semiconductor based storage device.

Fig. 10 illustrates yet another embodiment of the invention in the form of a program storage medium 1002 that includes a print job 1004. The  
15 print job 1004 includes PDL commands (i.e., computer readable code) that describes a document. The PDL commands includes a named sequence and also define an optimization parameter for the named sequence.

The print job 1004 may be expressed in any number of PDL languages. In this example, the language is POSTSCRIPT version 2 or higher.  
20 As is well known in the art, these versions of POSTSCRIPT use the form dictionary and resource operators in order to define a named sequence. In addition, the syntax of the POSTSCRIPT dictionary provides the means to define a additional key/value pair. Table 4 illustrates a portion of the print job 1004 to show how this POSTSCRIPT utility can be used to define an optimization  
25 parameter



---

	/DictionaryName	
	< <	
	/FormType 1	%POSTSCRIPT required key/value pair
5	/Matrix [ Matrix value field]	%POSTSCRIPT required key/value pair
	/Bbox [ Bbox value field]	%POSTSCRIPT required key/value pair
	/optimization_parameter (parameter value field)	% POSTSCRIPT additional Key/value % for passing optimization parameter % to printer
10	/PaintProc { body of named sequence placed here}	% POSTSCRIPT required key/value pair
	bind	

---

TABLE 4

Thus, for example, the parameter value field can be set to the pre-  
15 defined values from TABLE 1 to direct a printer to process the named sequence according to an optimum algorithm for a given situation.

In the embodiments described above, a parameter value was used as an indicator to indicate the information described in Table 1. It is understood, however, that this same information may be communicated using  
20 other types of indicators, such as specific predefined PDL commands. For example, a first command may be defined to indicate that permission is granted to print each instance of an associated form from the same video data. Another command may be defined to indicate that if new video data is generated to print each instance of an associated form, the new video data will, in each case, be  
25 identical. A third command may be defined to indicate that an associated named sequence represents a background image. A fourth command may be defined to indicate that each instance of the form is to be printed from the same video data.

Although a specific embodiment of the invention has been  
30 described and illustrated, the invention is not to be limited to the specific forms or arrangements of parts so described and illustrated. The invention is limited only by the claims and equivalents thereof.

## CLAIMS

What is claimed is:

- 1                    1.     A printer, comprising:  
2                    (a)     an I/O port capable of receiving a plurality of commands  
3     describing a document, the commands including both a named sequence  
4     describing a form and an indicator;  
5                    (b)     first means for responding to the indicator indicating  
6     permission is granted to print each instance of the form from the same video  
7     data, by processing and printing the named sequence according to a first  
8     printing algorithm.
- 1                    2.     The printer of claim 1, further comprising:  
2                    (c)     second means for responding to the indicator indicating  
3     each instance of the form is to be printed from new video data, by processing  
4     and printing the named sequence according to a second printing algorithm
- 1                    3.     The printer of claim 2, further comprising:  
2                    (d)     third means for responding to the indicator indicating that  
3     the form is a fixed form, by processing and printing the named according to a  
4     third algorithm.
- 1                    4.     The printer of claim 3, further comprising:  
2                    (e)     fourth means for responding to the indicator indicating that  
3     the form is a background image, by applying a fourth printing algorithm to  
4     process and print the named sequence.
- 1                    5.     The printer of claim 1, wherein the plurality of commands  
2     are received from a computer externally connected to the I/O port.
- 1                    6.     The printer of claim 5, wherein the indicator is generated by  
2     the computer.

1                   7.     The printer of claim 4, wherein the plurality of commands  
2     are received from an externally connected source.

1                   8.     In a printer, a method of processing and printing a named  
2     sequence describing a form, comprising:

3                   (a)     receiving the named sequence and an associated parameter;

4                   (b)     responding to the parameter being set to a first value,  
5     indicating permission is granted to print each instance of the form from the  
6     same video data, by converting the named sequence into video data and then  
7     using the video data to print each instance of the form.

1                   9.     The method of claim 8, further comprising:

2                   (c)     responding to the parameter being set to a second value,  
3     indicating that each instance of the form is to be printed from new video data,  
4     by generating new video data to print each instance of the form.

1                   10.    The method of claim 8, further comprising:

2                   (c)     responding to the parameter being set to a second value,  
3     indicating each instance of the form is to be printed from new video data, by  
4     converting the named sequence into display list data and then using the display  
5     list data to print each instance of the form.

1                   11.    The method of claim 9, wherein the plurality of commands  
2     are received from a source externally connected to the printer.

1                   12.    The method of claim 10, wherein the plurality of commands  
2     are received from a source externally connected to the printer

1                   13.    The method of claim 12, wherein step (c) comprises the  
2     following substep:

3                   (c.1)   flagging the display list data as a candidate for caching.

1                   14.    A computer, comprising:  
2                   (a)    means for generating a plurality of commands describing a  
3 document, the commands including both a named sequence describing a form  
4 and at least one command indicating permission is granted to convert the  
5 named sequence once into video data and to then print each instance of the  
6 form from the video data; and  
7                   (b)    means for transmitting the plurality of commands to a  
8 printer.

1                   15.    The computer of claim 14, further comprising:  
2                   (c)    means for generating a second plurality of commands  
3 describing a second document, the commands including a second named  
4 sequence describing a form and at least one command indicating new video  
5 data is to be generated to print each instance of the form.

1                   16.    The computer of claim 14, further comprising:  
2                   (d)    means for generating a third plurality of commands  
3 describing a third document, the commands including a third named sequence  
4 describing a form and at least one command indicating the form is fixed form.

1                   17.    The computer of claim 14, further comprising:  
2                   (e)    means for generating a fourth plurality of commands  
3 describing a fourth document, the commands including a fourth named  
4 sequence describing a form and at least one commands indicating the form  
5 represents a background image.

1                   18.    The computer of claim 14, wherein the printer is responsive  
2 to the plurality of commands by printing the document.

1                   19.    The computer of claim 14, wherein the printer is connected  
2 to the computer over a network.

1                   20.    The computer of claim 14, wherein the plurality of  
2 commands form a print job.

## ABSTRACT

A printing system for printing documents that includes a recurring image. The printing system includes a computer connected to a printer over a communication link. The computer generates a named sequence to represent the recurring image and a parameter. The parameter value provides the printer  
5 with information that can be used to optimize the processing and printing of the named sequence.




FIG. 1






FIG. 2




**FIG. 3**





**FIG. 4**



**FIG. 5**





FIG. 6



**FIG. 7**

FIG. 8 is a schematic diagram of a system 802, which includes a first page 804 and a second page 806. The first page 804 includes a first form A 804, a second form A 806, and a third form A 808. The second page 806 includes a fourth form A 810.





FIG. 8





**FIG. 10**

DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATIONATTORNEY DOCKET NO. 10991929-1

As a below named inventor, I hereby declare that:

My residence/post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**System For Printing A Document With Recurring Images**

the specification of which is attached hereto unless the following box is checked:

( ) was filed on \_\_\_\_\_ as US Application Serial No. or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understood the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose all information which is material to patentability as defined in 37 CFR 1.56.

**Foreign Application(s) and/or Claim of Foreign Priority**

I hereby claim foreign priority benefits under Title 35, United States Code Section 119 of any foreign application(s) for patent or inventor(s) certificate listed below and have also identified below any foreign application for patent or inventor(s) certificate having a filing date before that of the application on which priority is claimed:

COUNTRY	APPLICATION NUMBER	DATE FILED	PRIORITY CLAIMED UNDER 35 U.S.C. 119
			YES: _____ NO: _____
			YES: _____ NO: _____

**Provisional Application**

I hereby claim the benefit under Title 35, United States Code Section 119(e) of any United States provisional application(s) listed below:

APPLICATION SERIAL NUMBER	FILING DATE

**U. S. Priority Claim**

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

APPLICATION SERIAL NUMBER	FILING DATE	STATUS (patented/pending/abandoned)

**POWER OF ATTORNEY:**


As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Customer Number **022879**Place Customer  
Number Bar Code  
Label hereSend Correspondence to:  
**HEWLETT-PACKARD COMPANY**  
Intellectual Property Administration  
P.O. Box 272400  
Fort Collins, Colorado 80528-9599**Direct Telephone Calls To:****Matthew L. Wade**  
**(208) 396-5263**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Inventor: **Terry A. Smith**Citizenship: **US**Residence: **10699 W. Barnsdale Court, Boise, ID 83713**Post Office Address: **Same as residence**

Inventor's Signature



Date

**July 21, 2000**



**DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION (continued)**

ATTORNEY DOCKET NO. 10991929-1

Full Name of # 2 joint inventor: John F. Mauzey Citizenship: US

Residence: 11020 W. Amity Road, Boise, ID 83709

Post Office Address: Same as residence

John F. Mauzey  
Inventor's Signature

July 21, 2008  
Date

Full Name of # 3 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 4 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 5 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 6 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 7 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date

Full Name of # 8 joint inventor: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Residence: \_\_\_\_\_

Post Office Address: \_\_\_\_\_

\_\_\_\_\_  
Inventor's Signature Date